


8 7 6 5 4 3 2 1

ITEM	QTY -041	P/N	DESCRIPTION
X	D3695-041		SLIDER ASSEMBLY
1	1	D3695-1	SLIDER
2	1	D3695-3	STOPPER
3	1	D3801-1	HAND RETRACTABLE SPRING PLUNGER
4	4	MS21209F1-20	HELI-COIL, SCREW LOCKING (RED)
5	1	MS21209F6-25	HELI-COIL, SCREW LOCKING (RED)
6	4	MS24693-C276	SCREW




D3695-041 SLIDER ASSEMBLY


D3695-041 NOTES:

- 1) MATERIAL: NONE
- 2) FINISH: NONE
- 3) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED
- 4) UNITS: INCHES UNLESS OTHERWISE NOTED
- 5) BREAK SHARP EDGES:N/A
- 6) IDENTIFICATION: IDENT P/N "D3695-041" PER QSI 044 6.1
- 7) WEIGHT: D3695-041 = 0.63 lbs


E	ADDED R0.93 (ZN C8-3). REASON: PAR12-177.	MB	12.06.27
D	NOTE 6 UPDATED PER QSI. DIM 0.994 ^{+0.000} WAS 1.000 ^{+0.000} & 0.503 WAS 0.500 (ZN C6-2). REF NCR 10-324. CHAMFER ADDED TO D3695-1 (ZN C5-2)	JPH	10.09.24
C	UPDATED BOM TO CURRENT STANDARDS; REVISED ITEM 12 (ZN D3-1): DIMS 1.83 AND 1.075 ^{+0.010} WERE 1.81 AND 1.063 ^{+0.010} (ZN B8-3 AND C4-3). REASON: COMPENSATE FOR PAINT THICKNESS AND ELIMINATE RATTLE UPON ASSEMBLY.	MB	08.11.04
B	P/N D3808-1 WAS WIP-510 (ZN C7-1 AND D3-1) - REASON: PURCHASED PARTS NOW PROCURED THROUGH D3801 SPEC CONTROL DRAWING	MB	08.06.26
A	NEW ISSUE	MB	08.03.14
REV.	DESCRIPTION	BY	DATE
DESIGN		DART AEROSPACE LTD	
DRAWN		HAWKESBURY, ONTARIO, CANADA	
CHECKED		DRAWING NO.	REV. E
MFG. APPR.		D3695	SHEET 1 OF 3
APPROVED		TITLE	SCALE
DE APPR.		SLIDER ASSEMBLY	NTS
DATE	12.06.27	COPYRIGHT © 2008 BY DART AEROSPACE LTD THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.	



D3695-1 SLIDER



SECTION A-A






RELEASED
R 2012-07-16
[Signature]

D3695-1 NOTES:

- 1) MATERIAL: 6061-T6 (OR 6061-T651/-T6510/-T6511/-T62) BAR PER AMS-QQ-A-225/8 (OR AMS 4117/4128/4115/4116) OR PER AMS-QQ-A-200/8 (OR AMS 4160) (REF. DART SPEC. M6061T6B)
- 2) FINISH: CHEMICAL CONVERSION COAT PER DART QSI 005 4.1 POWDER COAT GREY SANTEX (4.3.5.6) PER DART QSI 005 4.3 - MASK ALL HOLES AND UNHATCHED AREAS
- 3) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED
- 4) UNITS: INCHES UNLESS OTHERWISE NOTED
- 5) BREAK SHARP EDGES: 0.005 TO 0.010 MAX
- 6) IDENTIFICATION: NONE
- 7) WEIGHT: 0.43lbs



DESIGN	<i>[Signature]</i>	DART AEROSPACE LTD
DRAWN	<i>[Signature]</i>	HAWKESBURY, ONTARIO, CANADA
CHECKED	<i>[Signature]</i>	DRAWING NO.
MFG. APPR.	<i>[Signature]</i>	D3695 REV. E
APPROVED	<i>[Signature]</i>	SHEET 2 OF 3
DE APPR.	<i>[Signature]</i>	TITLE
		SLIDER ASSEMBLY
DATE	12.06.27	SCALE

COPYRIGHT © 2008 BY DART AEROSPACE LTD
THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS
NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT
WRITTEN PERMISSION FROM DART AEROSPACE LTD.



D3695-3 STOPPER

RELEASED
2012-07-16



SECTION B-B

SECTION C-C

D3695-3 NOTES:

- 1) MATERIAL: 6061-T6 (OR 6061-T651/-T6510/-T6511/-T62) BAR PER AMS-QQ-A-225/8 (OR AMS 4117/4128/4115/4116) OR PER AMS-QQ-A-200/8 (OR AMS 4160) (REF. DART SPEC. M6061T6B)
- 2) FINISH: CHEMICAL CONVERSION COAT PER DART QSI 005 4.1 POWDER COAT GREY SANTEX (4.3.5.6) PER DART QSI 005 4.3
- 3) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED
- 4) UNITS: INCHES UNLESS OTHERWISE NOTED
- 5) BREAK SHARP EDGES: 0.005 TO 0.010 MAX
- 6) IDENTIFICATION: NONE
- 7) WEIGHT: 0.19 lbs

DESIGN	<i>[Signature]</i>	DART AEROSPACE LTD
DRAWN	<i>[Signature]</i>	HAWKSLEY, ONTARIO, CANADA
CHECKED	<i>[Signature]</i>	DRAWING NO.
MFG. APPR.	<i>[Signature]</i>	D3695
APPROVED	<i>[Signature]</i>	REV. E
DE APPR.	<i>[Signature]</i>	SHEET 3 OF 3
DATE	12.06.27	SCALE
		NTS
TITLE SLIDER ASSEMBLY		
COPYRIGHT © 2008 BY DART AEROSPACE LTD		
THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.		